



VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
C.F./P.IVA/ R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.
www.valpaint.it E-mail: info@valpaint.it

SC 00222

ADDITIVO SILVER G 200

Technical Sheet:

NAME:

ADDITIVO SILVER G 200

TYPE:

Water-based silver additive

USE:

To be added to Klondike to get silvery shadows

CHARACTERISTICS:

specific weight: 1.070± 30 gr/LT. a 25°C

viscosity: = = =

yield: LT. 0,100 per LT. 1 of Klondike
LT. 0,250 per LT. 2,5 of Klondike

aesthetic effect: silvery reflections

colours: silver like

packaging: LT. 0,100 - LT. 0,250

DRYING:

on surface: = = =

over painting: = = =

in depth: = = =

CHARACTERISTICS AND

RESISTANCE:

product stable to light and resistant to washing . Add to Klondike silvery reflections to the paint.

PREPARATION OF THE

= = =

SUPPORT:

PREPARATION OF THE

dilution: ready to use. Add to Klondike and mix well

PRODUCT:

catalization relation: = = =

pot life: = = =

APPLICATION:

system : add the Additive Silver G 200 in Klondike already coloured can and mix well

number of coating: = = =

NOTES:

- Working tools must be washed carefully soon after use with water
- Storage and application temperature must be superior to +5°C and inferior +30°C.

Technical Sheet n° SC 00222 issued by the Control Responsible of Quality

Edition n° 1

December 2009