



VALPAIN S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00136

CATALIZZATORE Z 50

Technical Sheet

NAME:

TYPE:

USE

TECHNICAL DATA:

CATALIZZATORE Z 50

organic and inorganic hardening products
to catalyse Sigillante Zot S 300

specific weight: 1.560 ± 30 gr/LT. at 25°C

viscosity: = = =

yield: = = =

aesthetic effect: = = =

colours: black

packaging: LT. 0,420

on the surface: = = =

over painting: = = =

below the surface: = = =

= = =

DRYING TIME:

CHARACTERISTICS AND

RESISTANCE:

PREPARATION OF THE

SURFACE:

PREPARATION OF THE

PRODUCT:

dilution: ready to use

catalization relation: Sigillante Zot S 300 100 parts
Catalizzatore Z 50 15 parts

pot life: = = =

system: = = =

number of coats: = = =

APPLICATION:

NOTE:

It is recommended to close the can after use to avoid products damaging. Before use it is absolutely necessary to stir perfectly Catalizzatore Z 50 in its can.

Technical Sheet n° SC 00136 issued by Control Quality Department:

Edition n° 1

October 2002