



VALPAINT S.p.A.
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384
E-mail: info@valpaint.it
C.F./P.IVA/R.I. di AN 01108220425
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00054

DILUENTE POLIURETANICO SERIE MB

TECHNICAL SHEET

NAME:

TYPE:

USE:

TECHNICAL DATA:

DRYING TIME:

CHARACTERISTICS AND

RESISTANCE:

PREPARATION OF THE

SURFACE:

PREPARATION OF THE

PRODUCT:

APPLICATION:

DILUENTE SERIE MB

organic diluents

polyurethane diluent's of universal use; the temperature has to be up to +10°C but not over + 25°C

specific weight: = = =

viscosity: = = =

yield: = = =

aspect: = = =

colours: = = =

packaging: cans of lt. 5 - lt. 10

on the surface: = = =

over painting: = = =

below the surface: = = =

= = =

= = =

thinning: = = =

catalization relation: = = =

pot life: = = =

system: = = =

coats: = = =

NOTE:

Keep in closed cans so that damp doesn't filtrate; keep in ventilated, protected to the sun and to the damp place.

Technical Sheet n° SC 00054 issued by the Control Quality Dpt.:

Edition n° 4

May 2002