



VALPAIN S.p.A.  
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY  
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384  
E-mail: info@valpaint.it  
C.F./P.IVA/R.I. di AN 01108220425  
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00049

## FONDO M PER GRANITONE

### TECHNICAL SHEET:

**NAME:**

**TYPE:**

**USE:**

**TECHNICAL DATA:**

**FONDO M PER GRANITONE**

opaque paints

specific primer for Granitone

**specific weight:** 1000 ±30 gr/LT at 25°C

**viscosity:** = = =

**yield:** 8-10 m<sup>2</sup>/LT

**aspect:** opaque

**colours:** see catalogue

**packaging:** cans of lt. 1 - lt. 5

**on the surface:** 2 hours at 20°C

**over painting:** 4 hours at 20°C

**below the surface:** 24 hours at 20°C

**DRYING TIME:**

**CHARACTERISTICS AND**

**RESISTANCE:**

**PREPARATION OF THE**

**SURFACE:**

the aim of Fondo M is to make the surfaces suitable for the application of the Granitone.

may be applied on several surfaces like plaster, wall, wood, iron opportunely treated, etc. Remove old and not anchored paints: plast, sand, clean the surface and then apply Fondo M by spray

**PREPARATION OF THE**

**PRODUCT:**

**thinning:** ready for use; dilute with Diluente Sintetico if necessary

**catalization relation:** = = =

**pot life:** = = =

**APPLICATION:**

**system:** spray gun - brush

**coats:** 1

### NOTE

Application and storage temperature from +5°C up to +35°C.

Technical Sheet n° SC 00049 issued by the Control Quality Technician:

Edition n° 2

May 2001