



VALPAINT S.p.A.  
Via dell'Industria, 80 - 60020 POLVERIGI (AN) ITALY  
Tel. +39 071 906383 (r.a.) - Fax +39 071 906384  
E-mail: info@valpaint.it  
C.F./P.IVA/R.I. di AN 01108220425  
Capitale Sociale € 500.000,00 i.v.

www.valpaint.it

SC 00179

## SETOMAT

### Technical Sheet

**NAME:**

**TYPE:**

**USE**

**CHARACTERISTICS:**

**SETOMAT**

water-based additive

additive to add to VALSETIN

**specific weight:** 2.000 ± 30 gr/LT. at 20°C

**viscosity:** = = =

**yield:** LT. 0,100 per LT. 1 of VALSETIN

LT. 0,400 per LT. 4 of VALSETIN

**aesthetic effect:** = = =

**colours:** = = =

**packaging:** LT. 0,100 - LT. 0,400

**on the surface:** = = =

**over painting:** = = =

**in depth:** = = =

**DRYING:**

**CHARACTERISTICS AND RESISTANCE:**

water-based additive to add to VALSETIN to get the particular Wallpaper Silk Effect and the Flowered Silk Effect as stated in VALSETIN catalogue.

**PRODUCT PREPARATION:**

= = =

**dilution:** ready to use; add to VALSETIN mixing carefully.

**catalisation relation:** = = =

**pot life:** = = =

**APPLICATION:**

**system :** Add a package of LT. 0,400 of SETOMAT, to LT. 4 of VALSETIN already coloured, or pour LT. 0,100 of SETOMAT in one package of LT. 1 of VALSETIN.

**number of coatings:** = = =

**NOTE:** The temperature of application and of stocking must not be inferior to +5°C and superior to +30°C. It is suggested to keep away from the sun and from the frost. Tools must be cleaned soon after use with water and soap.

Technical Sheet n° SC 00179 issued by the Control Quality Department

Edition n° 2

April 2005